

**NATURAL RESOURCES CONSERVATION SERVICE
CONSERVATION PRACTICE STANDARD
*SOUTH DAKOTA SUPPLEMENTS ITALICIZED***

STRUCTURE FOR WATER CONTROL

(no.)
CODE 587

DEFINITION

A structure in an irrigation, drainage, or other water management system that conveys water, controls the direction or rate of flow, or maintains a desired water surface elevation.

PURPOSE

To control the stage, discharge, distribution, delivery, or direction of flow of water in open channels or water use areas. Also used for water quality control, such as sediment reduction or temperature regulation. These structures are also used to protect fish and wildlife and other natural resources.

This standard applies to the structures normally installed in a well-planned irrigation or drainage system, wildlife facility or other water management systems for the conveyance, flow control, or level regulation of water. It covers the planning and functional design of such water-control structures but not the detailed design criteria or construction specifications for specific structures. It does not apply to structural components of irrigation pipelines or to Subsurface Drains or Grade Stabilization Structures (410).

CONDITIONS WHERE PRACTICE APPLIES

This practice applies wherever a permanent structure is needed as an integral part of an irrigation, drainage, or other water-control systems to serve one or more of the following functions:

1. To conduct water from one elevation to a lower elevation within, to, or from a ditch, channel, or canal. Typical structures: drops, chutes, turnouts, surface water inlets, head gates, pump boxes, and stilling basins.

2. To control the elevation of water in drainage or irrigation ditches. Typical structure: checks.
3. To control the division or measurement of irrigation water. Typical structures: division boxes and water measurement devices.
4. To keep trash, debris, or weed seeds from entering pipelines. Typical structure: debris screens.
5. To control the direction of channel flow resulting from tides and high water or backflow from flooding. Typical structure: tide and drainage gates.
6. To control the level of a water table or to remove surface or subsurface water from adjoining land, to flood land for frost protection or to manage water levels for wildlife or recreation. Typical structures: water level control structures, pipe drop inlets, and box inlets.
7. To provide water control for recreation or similar purposes.
8. To convey water over, under, or along a ditch, canal, road, railroad, or other barriers. Typical structures: bridges, culverts, flumes, inverted siphons.
9. To modify water flow to provide habitat or fish, wildlife, and other aquatic animals. Typical structures: deflectors, chutes, cold water release, or structures to make pools and riffles.

CONSIDERATIONS

Water Quantity

1. Effects on the water budget, especially on volumes and rates of runoff, infiltration, evaporation, transpiration, deep percolation, and ground water recharge.

Conservation practice standards are reviewed periodically and updated if needed. The current version of this standard is posted on our website at www.sd.nrcs.usda.gov or may be obtained at your local Natural Resources Conservation Service.

2. Potential for a change in the rate of plant growth and transpiration because of changes in the volume of soil water.
3. Effects on downstream flows or aquifers that would affect other water uses or users.
4. Effects on the volume of downstream flow that might cause environmental, social or economic effects.
5. The effect on the water table of the field to ensure that it will provide a suitable rooting depth for the anticipated crop.
6. Potential use for irrigation management to conserve water.

Water Quality

1. Effects on erosion and the movement of sediment and soluble and sediment-attached substances carried by runoff.
2. Effects on the movement of dissolved substances below the root zone and to ground water.
3. Short term and construction-related effects of this practice on the quality of downstream water.
4. Effects of water level control on the temperatures of downstream waters for their effects on aquatic and wildlife communities.
5. Effects on wetlands or water-related wildlife habitats.
6. Effects on the visual quality of downstream water resources.

Laws and Regulations

This practice must conform to all federal, state, and local laws and regulations. Laws and regulations of particular concern include those involving water rights, land use, pollution control, property easements, wetlands, preservation of cultural resources, and endangered species.

CRITERIA

Structures shall be designed on an individual job basis, or applicable standard drawings shall be adapted, to meet site conditions and functional requirements. They shall be part of an approved and overall engineering plan for irrigation, drainage, wildlife, recreation, channel improvement, or similar purposes.

The plan shall specify the location, grades, dimensions, materials, and hydraulic and structural requirements for the individual structure.

Provisions must be made for necessary maintenance. Care must be used to insure that the area's visual resources are not damaged. If watercourse fisheries are important, special precautions or design features may be needed to insure continuation of fish migrations.

If soil and climatic conditions permit, a protective cover of vegetation shall be established on all disturbed earth surfaces. If soil or climatic conditions preclude the use of vegetation and protection is needed, nonvegetative means, such as mulches or gravel, may be used. In some places, temporary vegetation may be used until permanent vegetation can be established. The structure can be fenced, if necessary, to protect the vegetation. Seedbed preparation, weeding, fertilizing, and mulching shall comply with the instructions in Technical Guides.

Foundation. *Necessary foundation investigations shall be made. The extent of these investigations will depend on the size and importance of the structures, the geology of the area, and the initial findings of the investigation. The foundation material shall have the required supporting strength, adequate resistance to sliding and piping, and should be reasonably homogeneous so as to prevent differential or uneven settlement of the structure.*

Capacity. *Structures shall have the capacity required to carry the design flow safely, control erosion, remain stable, and keep the upstream water surface within the limits allowed.*

PLANS AND SPECIFICATIONS

Plans and specifications for installing structures for water control shall be in keeping with this standard and shall describe the requirements for applying the practice to achieve its intended purpose.

OPERATION AND MAINTENANCE

A plan of operation and maintenance shall be prepared for use by the owner or others responsible for the system to insure that each component functions