

COMPOSTING FACILITY

(No.)
Code 317

Natural Resources Conservation Service
Conservation Practice Standard

I. Definition

A structure or device to contain and facilitate the controlled aerobic decomposition of manure or other organic material by micro-organisms into a biologically stable organic material that is suitable for use as a soil amendment.

II. Purpose

To reduce the pollution potential and improve the handling characteristics of organic waste solids; and produce a soil amendment that adds organic matter and beneficial organisms, provides slow-release plant-available nutrients, and improves soil condition.

III. Conditions Where Practice Applies

This practice applies where:

Organic waste material is generated by agricultural production or processing.

The facility is a component of a planned waste management system;

The facility can be constructed, operated and maintained without polluting air and/or water resources; and,

The compost can be applied to the land or marketed to the public.

IV. Federal, Tribal, State, and Local Laws

Users of this standard should be aware of potentially applicable federal, tribal, state and local laws, rules, regulations or permit requirements governing composting facilities. This standard does not contain the text of federal, tribal, state, or local laws.

V. Criteria

A. General Criteria Applicable to All Purposes

Safety. Incorporate safety and personal protection features and practices into the facility and its operation as appropriate to minimize the occurrence of equipment and biosecurity hazards during the composting process.

Facility Siting. Locate the composting facility on a base of low permeability soils, concrete, or other liner material that will not allow contamination of groundwater. The facility (except in-vessel composters) shall meet the Wisconsin NRCS Field Office Technical Guide (FOTG) Standard 313, Waste Storage Facility, "Specific Criteria for Permanent Facilities to Stack Confined Solid Manure and Derivatives."

Locate composting facilities above the 100-year floodplain elevation or protect the facility from inundation or damage from a 25-year flood event.

Locate so that prevailing winds and landscape elements minimize odors and protect visual resources.

Composting facilities shall be located 250 feet from any private well. Wisconsin Administrative Code Chapter NR 502 contains additional set back distances based on facility type and compost volume.

Direct surface runoff away from the compost facility. Direct contaminated runoff from the composting operation to an appropriate storage or treatment facility for further management.

Locate so that water is available to the facility during dry periods to ensure proper moisture and acceptable curing times to meet the management goals.

Facility Type. Select the type of composting facility or method based on the type and availability of raw material, the desired quality of finished compost, equipment, labor, time and land available.

Design of all structural components integral to the composting facility shall meet the structural loads and design criteria as described in Wisconsin NRCS FOTG, Section IV, Standards 313, Waste Storage Facility; 561, Heavy Use area Protection; and 367, Roofs and Covers, as applicable.

Compost Mix. Develop a compost mix that encourages aerobic microbial decomposition and avoids nuisance odors. The initial compost mix shall result in a carbon to nitrogen (C:N) ratio between 25:1 and 40:1.

Maintain adequate moisture in the compost mix throughout the compost period within the range of 40 to 65 percent (wet basis). Prevent excess moisture from accumulating in the compost.

Manage the compost to attain and then maintain the internal temperature for the duration required to meet management goals.

Facility Size. Size the composting facility to accommodate the amount of raw material planned for active composting, with a capacity consistent with the composting processes that will be used to produce the desired compost product, and with sufficient finishing time as required to achieve the desired characteristics. Space for compost storage may be included in the finishing space or in a separate facility. Select dimensions to accommodate handling and processing.

Compost Temperature Parameters. A facility for manure and other agricultural organic waste that is to be used on the farm shall have the capacity to produce compost that can be safely stored without undesirable odors. This requires the temperature of the compost to be maintained above 104°F for five days with at least four hours above 130°F during that time period.

A facility to produce compost for use off the farm or for sale shall have the capacity to significantly reduce pathogens. For a static pile or within vessel facility this requires the temperature of the compost to be maintained above 130°F for three days. The total compost period shall include time for the initial primary stage of composting and time for secondary stage composting. For a windrow system this requires the temperature of the compost to be above 130°F for 15 days with a minimum of five turnings of the compost.

If the facility is to be used to compost animal carcasses it shall have the capacity to maintain the compost temperature greater than 130° F for at

least 5 days as an average throughout the compost mass followed by a compatible time for secondary composting. For a windrow system the temperature of the compost shall be above 130°F for 15 days with a minimum of five turnings of the compost. Size animal mortality composting facilities according to the methods provided in the NRCS National Engineering Handbook (NEH) Part 637, Chapter 2, Composting; Part 651, Agricultural Waste Management Field Handbook, Chapter 10, Mortality Management, or comparable extension publication. Base the size of dead animal composting facilities on normal mortality loss records for the operation. If these data are not available use locally established mortality rates for the type of operation. Ensure that the final product of the composting process has no visible pieces of soft tissue remaining.

Use of Finished Compost. Land application of finished compost shall be in accordance with Wisconsin NRCS FOTG, Standard 590, Nutrient Management.

Compost may also be used for bedding and marketed off-farm.

VI. Considerations

To reduce offensive odors increase the carbon nitrogen ratio. A carbon nitrogen ration of 30:1 in the initial mix should have minimal odors.

Minimize odors and nitrogen loss by selecting carbonaceous material that, when blended with the nitrogenous material, provides a balance of nutrients and porous texture for aeration.

A chemical neutralizing or other additive agent should be used if structural components do not provide adequate odor reduction.

Maximize solar warming by aligning piles north to south configured with moderate side slopes.

Orient windrows to prevent ponding of surface runoff.

Protect compost facilities from the wind in cold or dry climates. Wind protection may help prevent excess drying of the compost.

Minimize blown in rain by providing roof overhang.

For facilities that are organic producers or that sell compost to organic producers, ensure that the

treated lumber used in the stacking facility meets the requirements for organic production. It may be best to have the producer consult with the organic certifier as to the use and acceptability of treated lumber for litter and compost storage.

VII. Plans and Specifications

Prepare plans and specifications in accordance with the criteria of this standard and describe the requirements for applying the practice to achieve its intended use, including:

- Layout and location of livestock facilities, waste collection points, and/or waste transfer
- Size, type and number of animals or other sources of organic feedstock
- Grading plan showing excavation, fill, and drainage, as appropriate
- Size and capacity needed
- Design requirements
- Safety requirement for operation

VIII. Operation and Maintenance

Develop an operation and maintenance plan (O&M) that is consistent with the purposes of this practice and the life of the composting facility. Compost recipe ingredients and the sequence that they are to be layered and mixed shall be given in the plan. Contents of the O&M plan shall include the following items.

Carbon Source. Store a dependable source of carbonaceous material with a high C:N ratio to mix with nitrogen rich waste materials.

Bulking Materials. Add bulking materials to the mix as necessary to enhance aeration. The bulking material may be the carbonaceous material used in the mix or a non-biodegradable material that is salvaged at the end of the compost period. Make provision for the salvage of any non-biodegradable material used in the composting process.

Temperature of Compost Mix. Closely monitor temperatures above 165°F. Take action immediately to cool piles that have reached temperatures above 185°F.

Turning/Aeration. The frequency of turning/aeration shall be appropriate for the composting method used, and to attain the desired amount of moisture removal and temperature control while maintaining aerobic degradation.

Monitoring: The operation and maintenance plan shall state that composting is a biological process that needs monitoring and management throughout the composting period to insure proper composting processes. The operation may need to undergo some trial and error in the start-up of a new composting facility. Manage the compost piles for temperature, odors, moisture, and oxygen, as appropriate. Test the finished compost as appropriate to assure that the required decomposition has been reached.

IX. References

USDA, NRCS. 2000. National Engineering Handbook, Part 637, Chapter 2, Composting. Washington, D.C.

USDA, NRCS Wisconsin Field Office Technical Guide (FOTG), Section IV, Practice Standards and Specifications.

Wisconsin Administrative Code, Department of Natural Resources, Chapter NR 502.